


## Uponor Vario M manifold with flowmeter FM 6xG3/4 Euro

1085948

- with flowmeter and eurocone thread



### Application information Uponor Vario M manifold with flowmeter FM

#### Specification

- Made of fibre glass reinforced polyamid
- With integrated valves
- Connection right or left G1 with flat sealing
- Supply bar with flowmeter for balancing and shut-off
- Return bar with return valves and caps
- Integrated airvents and fill&drain points in supply and return
- Loop connection: G3/4" eurocone
- Loop pitch: 50 mm

#### Application

- For underfloor heating and cooling
- Max. pressure: 6 bar at 60°C
- Combineable with actuators FT 30x1,5

## Uponor Vario M manifold with flowmeter FM 6xG3/4 Euro

1085948



### Measurements

Cylindric_thread_G	0,75
Cylindric_thread_G1	1
LENGTH_L	420
Length (l1)	85
Z Measurement b	50
Z Measurement b1	225
Z Measurement h	83
Z Measurement h1	34
Z Measurement h2	49
Z Measurement k	262
Z Measurement k1	312
Z Measurement w	353

### Product code

Item no EAN	4021598135574
Item no GF	35001085948
Item no GTIN	04021598135574

### Dimensions

Item Unit Height	85
Item Unit Length	420
Item Unit Weight	2,28
Item Unit Width	360
Item_UOM	pce

### Packaging

Packaging GTIN PL1	06414905471119
Packaging GTIN PL4	06414900329323
Packaging Height PL1	149
Packaging Height PL4	930

Packaging Length PL1	535
Packaging Length PL4	800
Packaging Quantity PL1	1
Packaging Quantity PL4	74
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,01466756
Packaging Volume PL4	0,8928
Packaging Weight PL1	2,69
Packaging Weight PL4	224,06
Packaging Width PL1	184
Packaging Width PL4	1200

## Documents

Page with all documents



### Uponor Corporation

Ilmalantori 4  
00240, Helsinki  
Finland

T +358 (0)20 129 211

[www.uponor.com](http://www.uponor.com)