

Uponor Smatrix Wave thermostat T-166 D RAL9016

1086982

- measures and displays the perceived room temperature
- operating distance: max. 30m
- protection class: IP30
- color: white glossy

- Functions:
 - heating or cooling demand indication
 - manual H/C changeover function (available with Uponor Smatrix Move only)
 - cooling allowed function (room by room)
 - displays celsius or fahrenheit
 - operating modes: room temperature (RT), internal with floor max/min (RFT), remote sensor (RS), remote outdoor (RO)
 - low battery indication
 - mode reception from timer
 - night set back
 - display with backlight (dims 10 seconds after last button event)
 - displays software version (on power-up)
 - compatible with Uponor Smatrix Move supply cont. X-157 Wired (1071693)
 - optional: floor sensor can be connected

- Consisting of:
 - Uponor Smatrix Wave thermostat digital T-166
 - 2x AAA batteries
 - mounting material



Application information Uponor Smatrix Wave thermostat T-166 D

Specification

- up to 4 controller in one system
- operating voltage: 230V
- autobalancing optimises energy use and comfort
- electric control
- supports up to 6 room thermostats and 8 actuators (24V) per controller
- pump and boiler relays
- valve and pump exercise
- relative humidity control
- combines underfloor heating/cooling and ceiling cooling control
- max. power input per actuator: 24VAC / 0.2A (0.4A peak)

Smatrix Wave Pulse:

- local access (Wi-Fi) or remote access (internet connection required) via Uponor Smatrix Pulse App (with R-208)
- temporary wi-fi access point for direct access (if local wi-fi is not available) (with R-208)
- smart home ecosystem integration (Amazon Alexa, Google Home) (with R-208)
- multi-home control (with R-208)
- third-party access for remote support (user allowance required) (with R-208)
- history trend analysis via Uponor Smatrix Pulse app (with R-208)
- timer programming (with R-208)
- comfort settings (with R-208)
- supply diagnostics (with R-208)

Application

- wireless room temperature control for radiant heating and cooling
- set point range: +5°C ... +35°C

Certification

- CE / EAC

Uponor Smatrix Wave thermostat T-166 D RAL9016

1086982

**Product code**

Item no EAN	4021598149120
Item no GTIN	04021598149120
Item no LVI	2024506
Item no NOBB	51166757
Item no NRF	8361082
Item no RSK	2987789
Item no VVS	466251023
Item Replacement 1	1144106

Dimensions

Item Unit Height	25
Item Unit Length	80
Item Unit Weight	0,116
Item Unit Width	80
Item_UOM	pce

Measurements

LENGTH_L	80
Z Measurement h	25
Z Measurement w	80

Packaging

Packaging GTIN PL1	06414905284658
Packaging GTIN PL3	06414905284665
Packaging GTIN PL4	06414905284672
Packaging Height PL1	40
Packaging Height PL3	300
Packaging Height PL4	1500
Packaging Length PL1	100
Packaging Length PL3	400

Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL3	75
Packaging Quantity PL4	1800
Packaging Type PL1	Base_Box
Packaging Type PL3	Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00036
Packaging Volume PL3	0,036
Packaging Volume PL4	1,44
Packaging Weight PL1	0,153
Packaging Weight PL3	11,62
Packaging Weight PL4	303,88
Packaging Width PL1	90
Packaging Width PL3	300
Packaging Width PL4	800

Status

Until stocks last

Until stocks last

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com