

## Uponor Smatrix Move PRO humidity sensor S-157

**1087160**

- room sensor + RH
- measures relative humidity for dew point calculations
- for cooling only and heating and cooling zones
- 3-wire connection to Uponor Smatrix Move PRO controller X-159
- humidity range: 0-100% non-condensing
- accuracy: < 2% RH
- operating voltage: 24V / 50-60 Hz
- operating temperature: -10°C ... +50°C
- protection class: IP20



## Application information Uponor Smatrix Move PRO humidity sensor S-157

### Specification

- multi-zone supply water temperature controls
- control up to 4 different supply water temperatures simultaneously
- intelligent auto heating/cooling changeover
- control snow/ice melting systems as well as turf heating
- integration with Smatrix Base PRO room controls possible
- optional connection to BMS via Modbus interface or R-147 KNX gateway (in combination with Smatrix Base PRO only)

### Application

- supply water
- commercial buildings
- indoor and outdoor
- radiant heating and cooling
- domestic hot water
- heating only mode
- heating and cooling

### Certification

- CE

## Uponor Smatrix Move PRO humidity sensor S-157

1087160



### Documents

Page with all documents



#### Uponor Corporation

Ilmalantori 4  
00240, Helsinki  
Finland

T +358 (0)20 129 211

[www.uponor.com](http://www.uponor.com)