

Uponor Smatrix Wave thermostat style T-169 black D+ RH

1087817

- measures and displays the perceived room temperature and relative humidity
- color: black

- Functions:
 - heating or cooling demand indication
 - RH measured value
 - comfort / ECO indication
 - ECO setback modification
 - manual H/C switchover function
 - cooling allowed function (room by room)
 - displays celsius or fahrenheit
 - operating modes: room temperature (RT), internal with floor max/min (RFT), remote sensor (RS), remote outdoor (RO)
 - low battery indication
 - temperature calibration
 - optional: floor, remote or outdoor sensor can be connected

- Consisting of:
 - Uponor Smatrix Wave thermostat D+RH Style T-169
 - 1x CR2032 battery
 - mounting material



Application information Uponor Smatrix Wave thermostat style T-169 black D+ RH

Specification

- up to 4 controller in one system
- operating voltage: 230V
- autobalancing optimises energy use and comfort
- electric control
- supports up to 6 room thermostats and 8 actuators (24V) per controller
- pump and boiler relays
- valve and pump exercise
- relative humidity control
- combines underfloor heating/cooling and ceiling cooling control
- max. power input per actuator: 24VAC / 0.2A (0.4A peak)

Smatrix Wave Pulse:

- local access (Wi-Fi) or remote access (internet connection required) via Uponor Smatrix Pulse App (with R-208)
- temporary wi-fi access point for direct access (if local wi-fi is not available) (with R-208)
- smart home ecosystem integration (Amazon Alexa, Google Home) (with R-208)
- multi-home control (with R-208)
- third-party access for remote support (user allowance required) (with R-208)
- history trend analysis via Uponor Smatrix Pulse app (with R-208)
- timer programming (with R-208)
- comfort settings (with R-208)
- supply diagnostics (with R-208)

Application

- wireless room temperature control for radiant heating and cooling
- set point range: +5°C ... +35°C

Certification

- CE / EAC

Uponor Smatrix Wave thermostat style T-169 black D+ RH

1087817



Product code

Item no EAN	4021598149847
Item no GF	35001087817
Item no GTIN	04021598149847
Item no LVI	2025247
Item no NOBB	51974383
Item no NRF	8361253
Item no RSK	2987819
Item no VVS	466251071

Dimensions

Item Unit Height	10
Item Unit Length	80
Item Unit Weight	0,042
Item Unit Width	80
Item_UOM	pce

Measurements

LENGTH_L	80
Z Measurement h	10
Z Measurement w	80

Packaging

Packaging GTIN PL1	06414905285532
Packaging GTIN PL3	06414900570442
Packaging GTIN PL4	06414900570435
Packaging Height PL1	20
Packaging Height PL3	200
Packaging Height PL4	950
Packaging Length PL1	100
Packaging Length PL3	400

Packaging Length PL4	1200
Packaging Material (number) PL1	20
Packaging Material (number) PL3	20
Packaging Material PL1	corrugated cardboard / cartone
Packaging Material PL3	corrugated cardboard / cartone
Packaging Material (short) PL1	PAP_C
Packaging Material (short) PL3	PAP_C
Packaging Quantity PL1	1
Packaging Quantity PL3	90
Packaging Quantity PL4	2880
Packaging Type PL1	BASE_BOX
Packaging Type PL3	BOX
Packaging Type PL4	PALLET
Packaging Volume PL1	0,00018
Packaging Volume PL3	0,024
Packaging Volume PL4	0,912
Packaging Weight PL1	0,068
Packaging Weight PL3	6,54
Packaging Weight PL4	221,78
Packaging Width PL1	90
Packaging Width PL3	300
Packaging Width PL4	800

Technical data

Recycling Text Block PL1	corrugated cardboard / cartone
Recycling Text Block PL3	corrugated cardboard / cartone

Documents

Page with all documents

Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com