Product data sheet



GF Uponor S-Press valve U-shaped 25

1089026

- Made of DR brass (lead-free)
- Contoured Aluminium-sleeve
- Fast 3-step installation (press without bevel)
- Colour code
- For cold and hot tap water application



Application information GF Uponor S-Press valve U-shaped

Specification

- with fixed press sleeve
- stop ring
- test safety

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

- if not different mentioned:
Male and female threads acc.to EN 10226-1.

Certification

- Approvals by local OM.
E.g.
- DVGW
- AENOR

GF Uponor S-Press valve U-shaped 25

1089026



Product code

Item no EAN	6414905212446
Item no GF	35001089026
Item no GTIN	06414905212446

Dimensions

Item Unit Height	90
Item Unit Length	67.5
Item Unit Weight	0,424
Item Unit Width	103
Item_UOM	pce

Measurements

LENGTH_L	106
Length (l1)	35,5
Length (l2)	50
Length (l3)	35,5
Z Measurement h	91,6
Z Measurement w	74
Z2	19,7

Packaging

Packaging GTIN PL1	06414905235124
Packaging GTIN PL2	06414905270651
Packaging GTIN PL3	06414905271733
Packaging GTIN PL4	06414905276059
Packaging Height PL1	90
Packaging Height PL2	150
Packaging Height PL3	305

Packaging Height PL4	1160
Packaging Length PL1	150
Packaging Length PL2	120
Packaging Length PL3	265
Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL2	5
Packaging Quantity PL3	30
Packaging Quantity PL4	720
Packaging Type PL1	Plastic_Bag
Packaging Type PL2	Medium_Box
Packaging Type PL3	Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00243
Packaging Volume PL2	0,00432
Packaging Volume PL3	0,03152175
Packaging Volume PL4	1,1136
Packaging Weight PL1	0,427
Packaging Weight PL2	2,235
Packaging Weight PL3	13,62
Packaging Weight PL4	351,88
Packaging Width PL1	180
Packaging Width PL2	240
Packaging Width PL3	390
Packaging Width PL4	800

Documents

Page with all documents

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E communications@georgfischer.com

www.uponor.com

+GF+