


Uponor S-Press valve U-shaped 16

1089028

- Made of brass
- Contoured Aluminium-sleeve
- Fast 3-step installation (press without bevel)
- Colour code
- For cold and hot tap water application



Application information Uponor S-Press valve U-shaped

Specification

- with fixed press sleeve
- stop ring
- test safety

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

- if not different mentioned:

Male and female threads acc.to EN 10226-1.

Certification


- Approvals by local OM.

E.g.

- DVGW
- AENOR

Uponor S-Press valve U-shaped 16

1089028



Status

Item Available Till date

2026-12-31T00:00:00.000+0100

Product code

Item no EAN	6414905212484
Item no GF	35001089028
Item no GTIN	06414905212484

Dimensions

Item Unit Height	86
Item Unit Length	56.6
Item Unit Weight	0,286
Item Unit Width	74
Item_UOM	pce

Measurements

LENGTH_L	74
Length (I1)	21
Length (I2)	39,1
Length (I3)	27
Z Measurement h	85
Z Measurement w	63,1
Z2	17,7

Packaging

Packaging GTIN PL1	06414905235148
Packaging GTIN PL2	06414905270675
Packaging GTIN PL3	06414905271757
Packaging GTIN PL4	06414905276073
Packaging Height PL1	86
Packaging Height PL2	150
Packaging Height PL3	305

Packaging Height PL4	1160
Packaging Length PL1	150
Packaging Length PL2	120
Packaging Length PL3	265
Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL2	10
Packaging Quantity PL3	60
Packaging Quantity PL4	1440
Packaging Type PL1	Plastic_Bag
Packaging Type PL2	Medium_Box
Packaging Type PL3	Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,002322
Packaging Volume PL2	0,00432
Packaging Volume PL3	0,03152175
Packaging Volume PL4	1,1136
Packaging Weight PL1	0,289
Packaging Weight PL2	2,99
Packaging Weight PL3	18,15
Packaging Weight PL4	460,6
Packaging Width PL1	180
Packaging Width PL2	240
Packaging Width PL3	390
Packaging Width PL4	800

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com