

Uponor Ecoflex wall through sealing 250

1090415

- For concrete-cast and brick walls
- Prevents moisture from entering the building
- Applicable for NWP = no pressurized water area



Application information Uponor Ecoflex wall through sealing

Specification

- All accessories are corrosion resistant.

Application

- Ecoflex accessories are designed to complete the assortment in buried installation.

Certification

- Approvals should be checked by local responsible person

Uponor Ecoflex wall through sealing 250

1090415

**Measurements**

Inner_diameter_di	250
LENGTH_L	50
Outer Diameter_do	300

Product code

Item no EAN	6414905218141
Item no GF	35001090415
Item no GTIN	06414905218141
Item no LVI	3010600
Item no NRF	8360507
Item no RSK	2282496
Item no VVS	087916025

Dimensions

Item Unit Height	300
Item Unit Length	300
Item Unit Weight	0,83
Item Unit Width	50
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905268863
Packaging Height PL1	300
Packaging Length PL1	300
Packaging Quantity PL1	1
Packaging Type PL1	Plastic_Bag
Packaging Volume PL1	0,0045
Packaging Weight PL1	0,836
Packaging Width PL1	50

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E
communications@georgfischer.
com