


Uponor Uni Pipe PLUS white insulated S6 WLS 040 20x2,25 blue 75m**1091724**

- coil
- Insulation thickness 6 mm
- thermal conductivity $\lambda=0,040$ W/m*k
- round extruded

**Application information Uponor Uni Pipe PLUS white insulated S6 WLS 040****Specification**

- Oxygen diffusion resistant multi-layer composite pipe (PE-RT - adhesive – seamless aluminium/longitudinally welded aluminium - adhesive - PE-RT) produced using SACP and OWC-technology.
- Fire classification E according to EN 13501-1.
- With pipe end caps as hygienic seal according EN 806.

Application


- Tested/Approved according EN ISO 21003 Multilayer piping systems for hot and cold water installations inside buildings for application class 1,2,4,5/10bar
- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

Certification

- Approvals by local OM.
- E.g.
- DVGW
 - AENOR

Uponor Uni Pipe PLUS white insulated S6 WLS 040 20x2,25 blue 75m

1091724



Product code

Item no EAN	6414905223565
Item no GF	35001091724
Item no GTIN	06414905223565

Dimensions

Item Unit Height	32
Item Unit Length	1000
Item Unit Weight	0,192
Item Unit Width	32
Item_UOM	m

Measurements

Length	75
Outer Diameter_do	20
Outer Diameter_do1	32
Wall thickness_s	2,25
Wall thickness_s1	6

Packaging

Packaging GTIN PL1	06414905269600
Packaging GTIN PL4	06414905277414
Packaging Height PL1	295
Packaging Height PL4	2000
Packaging Length PL1	780
Packaging Length PL4	1200
Packaging Quantity PL1	75
Packaging Quantity PL4	600
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,179478

Packaging Volume PL4	1,92
Packaging Weight PL1	16,35
Packaging Weight PL4	155,8
Packaging Width PL1	780
Packaging Width PL4	800

Documents

Page with all documents 

Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com