Product data sheet




GF Uponor Smatrix Wave controller Pulse X-265 6X

1093021

- compatible to Uponor Smatrix Wave controller Pulse X-265 6X
- protection class: Class II IP20
- color: white

- Consisting of:
- Uponor Smatrix Wave controller Pulse X-265 6X
- Uponor Smatrix Wave antenna Pulse A-265
- first step instructions, safety instructions
- mounting material



Application information GF Uponor Smatrix Wave controller Pulse X-265 6X

Specification

- modular system includes controller, expansion module, com module with app for mobile devices, relay modules, thermostats and sensors
- wireless connections with Smatrix Wave thermostats
- up tp 8 room thermostats and 10 actuators (24V) per controller
- up to 14 room thermostats and 16 actuators (24V) per controller with expansion module
- up to 4 controllers in one system, wireless connected
- pump and boiler relays (output) with every controller
- 4 outputs in total for systems with relay module M-161, configurable via app
- heating/cooling switch input
- heating/cooling change with thermostat T-267
- relative humidity control with thermostats and sensors
- combines underfloor heating/cooling and ceiling cooling control
- app for mobile devices with installation wizard and intuitive user interface
- on-site access with Bluetooth BLE for commissioning and service
- generating installation configurations for repeated use in the app
- remote access via app for internet connected systems
- Smatrix AI for energy savings in installations with heat pumps
- schedule settings, via app or programmable thermostat T-168
- comfort settings
- shut-off function for the seasonal transitional period
- valve and pump exercise
- fast automatic software updates
- supply diagnostics for internet connected systems
- color LEDs on controller providing status information
- operating voltage of controller 230V
- low voltage actuators: 24VAC /0.2A (0.4A peak)

Application


- wireless room temperature control for radiant heating and cooling
- set point range: +5°C ... +35°C

Certification

- CE, UKCA

GF Uponor Smatrix Wave controller Pulse X-265 6X

1093021



Status

Item Available Till date	2026-12-31T00:00:00.000+0100

Product code

Item no EAN	6414905228058
Item no GF	35001093021
Item no GTIN	06414905228058
Item no LVI	2024568
Item no NRF	8361139
Item no RSK	2988495
Item no VVS	466251310

Dimensions

Item Unit Height	50
Item Unit Length	370
Item Unit Weight	1,5620
Item Unit Width	110
Item_UOM	pce

Measurements

LENGTH_L	370
Z Measurement h	50
Z Measurement w	110

Packaging

Packaging GTIN PL1	06414905441532
Packaging GTIN PL2	06414905443291
Packaging GTIN PL4	06414905503902
Packaging Height PL1	80
Packaging Height PL2	300

Packaging Height PL4	1044
Packaging Length PL1	370
Packaging Length PL2	400
Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL2	4
Packaging Quantity PL4	96
Packaging Type PL1	Base_Box
Packaging Type PL2	Medium_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,004588
Packaging Volume PL2	0,036
Packaging Volume PL4	1,00224
Packaging Weight PL1	1,8700
Packaging Weight PL2	8,1600
Packaging Weight PL4	220,8400
Packaging Width PL1	155
Packaging Width PL2	300
Packaging Width PL4	800

Documents

Page with all documents

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E communications@georgfischer.com

www.uponor.com

+GF+