


Uponor Smatrix Wave starter set Pulse L

1093287

- ready-to-use carefree package with basic system setup for single family homes
- extendable on demand
- compatible to Uponor Smatrix Wave controller Pulse X-265 6X
- protection class: Class II IP20
- color: white

Consisting of:

- 1x Uponor Smatrix Pulse com R-208
- 2x Uponor Smatrix Wave controller Pulse X-265 6X
- 5x Uponor Smatrix Wave thermostat D+RH Style T-169
- first step instructions, safety instructions
- mounting material



Application information Uponor Smatrix Wave starter set Pulse L

Specification

- up to 4 controller in one system
- operating voltage: 230V
- autobalancing optimises energy use and comfort
- electric control
- supports up to 6 room thermostats and 8 actuators (24V) per controller
- pump and boiler relays
- valve and pump exercise
- relative humidity control
- combines underfloor heating/cooling and ceiling cooling control
- max. power input per actuator: 24VAC / 0.2A (0.4A peak)

Smatrix Wave Pulse:

- local access (Wi-Fi) or remote access (internet connection required) via Uponor Smatrix Pulse App (with R-208)
- temporary wi-fi access point for direct access (if local wi-fi is not available) (with R-208)
- smart home ecosystem integration (Amazon Alexa, Google Home) (with R-208)
- multi-home control (with R-208)
- third-party access for remote support (user allowance required) (with R-208)
- history trend analysis via Uponor Smatrix Pulse app (with R-208)
- timer programming (with R-208)
- comfort settings (with R-208)
- supply diagnostics (with R-208)

Application


- wireless room temperature control for radiant heating and cooling
- set point range: +5°C ... +35°C

Certification

- CE / EAC

Uponor Smatrix Wave starter set Pulse L

1093287



Technical data

Item (unit of measurement) set

Item no VVS 466251302

Item no LVI 2024572

Length (l) 385 mm

Z-measurement h 140 mm

Z-measurement w 285 mm

Packaging Quantity PL1 1

Packaging Quantity PL2 2

Packaging Quantity PL4 24

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E info@uponor.com
F +358 (0)20 129 2841

www.uponor.com