

Uponor Ecoflex Supra Pipe 32x2,9/68

1095723

- Cold potable water and cooling
- One medium pipe PE 100 RC black, SDR 11
- Max. load 16 bar / 20°C
- PEX foam, HDPE casing



Application information Uponor Ecoflex Supra Pipe

Specification

- Flexible, pre-insulated, self-compensating plastic pipe system
- Medium pipe: Polyethylene PE100 RC, PN 16 (SDR 11) black with blue stripes
- Insulating material: Closed-cell PE-X foam, permanently elastic, ageing-resistant
- Casing pipe: Corrugated polyethylene (HDPE)

Application


- Transport of cold potable or cooling water for buried installations.
- Operating temperature +20°C
- Static verification for heavy traffic load of 60 tons

Certification

- Approvals should be checked by local responsible person

Uponor Ecoflex Supra Pipe 32x2,9/68

1095723



Measurements

Bending radius M	0,4
Outer Diameter_do	68
Outer Diameter_do1	32
Wall thickness_s1	2,9

Product code

Item no EAN	6414905485611
Item no GF	35001095723
Item no GTIN	06414905485611
Item no NRF	8360518

Dimensions

Item Unit Height	68
Item Unit Length	1000
Item Unit Weight	0,62
Item Unit Width	68
Item_UOM	m

Packaging

Packaging GTIN PL1	06414905537891
Packaging Height PL1	1600
Packaging Length PL1	1600
Packaging Quantity PL1	200
Packaging Type PL1	Coil
Packaging Volume PL1	1,8944
Packaging Weight PL1	124
Packaging Width PL1	740

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E
communications@georgfischer.
com