


Uponor Ecoflex Supra 75x6,8/175

1095727

- Cold potable water and cooling
- One medium pipe PE 100 RC black, SDR 11
- Max. load 16 bar / 20°C
- PEX foam, HDPE casing



Application information Uponor Ecoflex Supra

Specification

- Flexible, pre-insulated, self-compensating plastic pipe system
- Medium pipe: Polyethylene PE100 RC, PN 16 (SDR 11) black with blue stripes
- Insulating material: Closed-cell PE-X foam, permanently elastic, ageing-resistant
- Casing pipe: Corrugated polyethylene (HDPE)

Application


- Transport of cold potable or cooling water for buried installations.
- Operating temperature +20°C
- Static verification for heavy traffic load of 60 tons

Certification

- Approvals should be checked by local responsible person

Uponor Ecoflex Supra 75x6,8/175

1095727



Measurements

Bending radius M	0,9
Outer Diameter_do	175
Outer Diameter_do1	75
Wall thickness_s1	6,8

Product code

Item no EAN	6414905485659
Item no GF	35001095727
Item no GTIN	06414905485659
Item no NRF	8361428

Dimensions

Item Unit Height	175
Item Unit Length	1000
Item Unit Weight	2,72
Item Unit Width	175
Item_UOM	m

Packaging

Packaging GTIN PL1	06414905537938
Packaging Height PL1	2200
Packaging Length PL1	2200
Packaging Quantity PL1	150
Packaging Type PL1	Coil
Packaging Volume PL1	6,292
Packaging Weight PL1	408
Packaging Width PL1	1300

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com