


Uponor RS adapter S-Press PLUS 25-RS2

1095819

- tin plated
- made of DR material
- press without bevel



Application information Uponor RS adapter S-Press PLUS

Specification

- with fixed press sleeve
- stop ring
- colour code
- Test safety

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

if not different mentioned:

- Male and female threads acc.to EN 10226-1.

Certification


- Approvals by local OM.

E.g.

- DVGW
- AENOR

Uponor RS adapter S-Press PLUS 25-RS2

1095819



Technical data

Item (unit of measurement)	pce
Item no VVS	045450325
Item no LVI	1720818
Item no NRF	5071228
Length (l)	75 mm
Length (l1)	20 mm
Length (l2)	28 mm
Packaging Quantity PL1	1
Packaging Quantity PL4	378

Documents

Page with all documents 

Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E info@uponor.com
F +358 (0)20 129 2841

www.uponor.com