

Uponor Ecoflex VIP Thermo Twin 2x50x4,6/175

1118583

- Heating and Cooling
- Two medium pipes PE-Xa with oxygen barrier, SDR11
- Max. Load 6 bar / 95°C
- Coloured centre profil to avoid confusion of flow and return line
- VIP+PEX foam, HDPE casing



Application information Uponor Ecoflex VIP Thermo Twin

Specification

- Flexible, pre-insulated, self-compensating plastic pipe system produced based on EN 15632 and EN 17414.
- Medium pipe: cross-linked polyethylene (PE-Xa) pipe based on EN ISO 15875, natural colored, PN 6 (SDR 11), Oxygen tightness based on EN 15632
- Insulating material: Revolutionary insulation material with extremely low lambda value in combination with permanently elastic closed-cell PE-X foam
- Casing pipe: Corrugated polyethylene (HDPE)

Application

- Transport of heating and cooling water for buried installations.
- Heating operating temperature 80°C based on EN 15632
- Malfunction temperature 95°C
- Static verification for heavy traffic load of 60 tons

Certification

- Approvals should be checked by local responsible person

Uponor Ecoflex VIP Thermo Twin 2x50x4,6/175

1118583



Measurements

Bending radius M	0,9
Outer Diameter_do	175
Outer Diameter_do1	50
Outer Diameter_do2	50
Wall thickness_s1	4,6
Wall thickness_s2	4,6

Product code

Item no EAN	6414905519132
Item no GF	35001118583
Item no GTIN	06414905519132
Item no LVI	3010245
Item no NRF	8360961
Item no RSK	2266370
Item no VVS	087808450
Item Replacement 1	1160613

Dimensions

Item Unit Height	175
Item Unit Length	1000
Item Unit Weight	3,44
Item Unit Width	175
Item_UOM	m

Packaging

Packaging GTIN PL1	06414905542567
Packaging Height PL1	2400
Packaging Length PL1	2400
Packaging Quantity PL1	200
Packaging Type PL1	Coil

Packaging Volume PL1	10,368
Packaging Weight PL1	688
Packaging Width PL1	1800

Status

Until stocks last	Until stocks last
-------------------	-------------------

Documents

Page with all documents 

Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com