
Product data sheet



GF Uponor S-Press PLUS sound + leak protect 16-20

1121193

- Set is suitable for two Uponor S-Press PLUS tap elbows 16-Rp1/2"FT or 20-Rp1/2"FT
- Pins and screws M6 x 16 included
- Made of EPP
- Sound protection acc., VDI 4100
- Drainage function conform to DIN 18534



Application information GF Uponor S-Press PLUS sound + leak protect

Specification

- Unique press indicator
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- Colour code
- Fixed press sleeve with insprection window
- Precise jaw fixation
- Fast diameter recognition
- Accurate test safety function
- 100% backward compatible with existing Uponor components
- Flow rate optimized fitting body

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

if not different mentioned:
- Male and female threads acc.to EN 10226-1.


Certification

- Approvals by local OM.

E.g.
- DVGW
- AENOR

GF Uponor S-Press PLUS sound + leak protect 16-20

1121193



Measurements

Inner_diameter_di	32,5
Length (l1)	23
Outer Diameter_do	48,5
Z Measurement k	40
Z Measurement w	96,5
Z Measurement w1	17,5
z1	6

Product code

Item no EAN	6414905641529
Item no GF	35001121193
Item no GTIN	06414905641529

Dimensions

Item Unit Height	104.5
Item Unit Length	55.5
Item Unit Weight	0,026
Item Unit Width	73
Item_UOM	set

Packaging

Packaging GTIN PL1	06414905663873
Packaging GTIN PL4	06414905663941
Packaging Height PL1	89
Packaging Height PL4	678
Packaging Length PL1	176
Packaging Length PL4	1200
Packaging Quantity PL1	1

Packaging Quantity PL4	192
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00211464
Packaging Volume PL4	0,65088
Packaging Weight PL1	0,06
Packaging Weight PL4	36,5
Packaging Width PL1	135
Packaging Width PL4	800

Documents

Page with all documents

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E communications@georgfischer.com

www.uponor.com

+GF+