

Uponor HypAir admittance valve 32-63

1134572

- Air admittance valve for sewage systems



Application information Uponor HypAir admittance valve

Specification

Uponor HypAir admittance valves are one-way valves designed to allow air to enter the sewage system when negative pressures develops in the piping system. Uponor HypAir admittance valves close by gravity and seal the vent at zero differential pressure (no flow conditions) and under positive internal pressures.

Application

Housing sewage system ventilation acc. to local standardisation.

Certification

Class AI acc EN 12380, TÜV certified.

Uponor HypAir admittance valve 32-63

1134572

**Measurements**

Inner_diameter_di1	40
Inner_diameter_di2	32
LENGTH_L	80
Length (l1)	35
Outer Diameter_do	70
Outer Diameter_do1	63
Outer Diameter_do2	-
Outer Diameter_do3	50

Product code

Item no EAN	6414900481069
Item no GF	35001134572
Item no GTIN	06414900481069
Item no LVI	4162841
Item no NRF	2217992
Item no RSK	3350920
Item no VVS	173941063

Dimensions

Item Unit Height	79.5
Item Unit Length	70
Item Unit Weight	0,1
Item Unit Width	70
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414900481090
Packaging GTIN PL2	06414900485104
Packaging GTIN PL4	06414900443753
Packaging Height PL1	81

Packaging Height PL2	345
Packaging Height PL4	1524
Packaging Length PL1	71
Packaging Length PL2	385
Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL2	100
Packaging Quantity PL4	2400
Packaging Type PL1	Base_Box
Packaging Type PL2	Medium_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,000408321
Packaging Volume PL2	0,051137625
Packaging Volume PL4	1,46304
Packaging Weight PL1	0,11
Packaging Weight PL2	11,9
Packaging Weight PL4	300
Packaging Width PL1	71
Packaging Width PL2	385
Packaging Width PL4	800

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com