
Product data sheet




GF Uponor Vario S manifold FM 11xG3/4 Euro - G1

1140842

- Supply beam with flowmeters for balancing and shutoff, with memory ring
- Return beam with valves for shutoff, with hand caps





Application information GF Uponor Vario S manifold FM

Specification


- Made of stainless steel
- With integrated valves
- Connection right or left with flat sealing
- Integrated airvents and fill&drain points in supply and return,
- Loop connection G3/4" eurocone
- Loop pitch 50 mm
- Header pitch 215 mm


Application

- For underfloor-heating and -cooling
- Applicable with actuators 1141676 (230V) and 1141677 (24V)
- Max. pressure: 6 bar at 60°C

GF Uponor Vario S manifold FM 11xG3/4 Euro - G1

1140842





Status

Item Available From date	2024-04-01

Product code

Item no EAN	6414900440493
Item no GF	35001140842
Item no GTIN	06414900440493
Item no LVI	2022299
Item no NRF	8361369

Dimensions

Item Unit Height	40
Item Unit Length	660
Item Unit Weight	6,5
Item Unit Width	235
Item_UOM	pce

Measurements

LENGTH_L	664
Length (l1)	77
Length (l2)	87
Z Measurement b	50
Z Measurement b1	217
Z Measurement h	73
Z Measurement h1	30
Z Measurement h2	50
Z Measurement k	585
Z Measurement k1	336
Z Measurement w	357

Packaging

Packaging GTIN PL1	06414900500814
Packaging GTIN PL4	06414900322973
Packaging Height PL1	47
Packaging Height PL4	996
Packaging Length PL1	767
Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL4	54
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,011463582
Packaging Volume PL4	0,95616
Packaging Weight PL1	6,6
Packaging Weight PL4	381,4
Packaging Width PL1	318
Packaging Width PL4	800

Documents

Page with all documents

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E communications@georgfischer.com

www.uponor.com

+GF+