


Uponor Vario S manifold LS 9xG3/4 Euro - G1

1140870

- Supply beam with lock shield valves for balancing and shutoff
- Return beam with valves for shutoff, with hand caps



Application information Uponor Vario S manifold LS

Specification


- Made of stainless steel
- With integrated valves
- Connection right or left with flat sealing
- Integrated airvents and fill&drain points in supply and return,
- Loop connection G3/4" eurocone
- Loop pitch 50 mm
- Header pitch 215 mm

Application

- For underfloor heating and cooling
- Applicable with actuators 1141676 (230V) and 1141677 (24V)
- Max. pressure: 6 bar at 60°C

Uponor Vario S manifold LS 9xG3/4 Euro - G1

1140870



Status

Item Available From date

2024-04-01

Product code

Item no EAN	6414900440776
Item no GF	35001140870
Item no GTIN	06414900440776
Item no LVI	2022253
Item no NRF	8361379
Item no VVS	046230109

Dimensions

Item Unit Height	40
Item Unit Length	560
Item Unit Weight	5,5
Item Unit Width	235
Item_UOM	pce

Measurements

Length (l1)	564
Length (l2)	87
Z Measurement b	50
Z Measurement b1	217
Z Measurement h	73
Z Measurement h1	30
Z Measurement h2	50
Z Measurement k	485
Z Measurement k1	336
Z Measurement w	357

Packaging

Packaging GTIN PL1

06414900500944

Packaging GTIN PL4	06414900323055
Packaging Height PL1	47
Packaging Height PL4	996
Packaging Length PL1	617
Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL4	54
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,009221682
Packaging Volume PL4	0,95616
Packaging Weight PL1	5,6
Packaging Weight PL4	327
Packaging Width PL1	318
Packaging Width PL4	800

Documents

Page with all documents 

Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E
communications@georgfischer.
com