


Uponor Vario manifold return valve M30x1,5

1140964

- For Vario S manifolds
- Connection to actuator: M30x1,5



Application information Uponor Vario manifold return valve

Specification


- Components made of brass, nickel-plated brass, steel, and engineered plastics
- Eurocone, threaded, and flat-sealing connections
- Compatible with Vario B, C, S, M, PLUS, and MAGNA manifolds
- Includes valves, flowmeters, air vents, actuators, and adapters
- Designed for heating and cooling applications

Application

- Completion and extension of Vario manifold installations
- Flow regulation, balancing, and shut-off
- Connection of PEX, MLCP, and composite pipes
- Integration of actuators, sensors, and control units
- Commissioning, maintenance, and system optimization

Uponor Vario manifold return valve M30x1,5

1140964



Measurements

Cylindric_thread_G	1/2
LENGTH_L	68,6
Length (l1)	40,8
Outer Diameter_do	35,8

Product code

Item no EAN	6414900499019
Item no GF	35001140964
Item no GTIN	06414900499019
Item no LVI	2022269
Item no NRF	8361385
Item no VVS	046230426

Dimensions

Item Unit Height	30
Item Unit Length	55
Item Unit Weight	0,16
Item Unit Width	30
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414900501187
Packaging GTIN PL2	06414900501200
Packaging Height PL1	31
Packaging Height PL2	150
Packaging Length PL1	120
Packaging Length PL2	150
Packaging Quantity PL1	1
Packaging Quantity PL2	20
Packaging Type PL1	Plastic_Bag

Packaging Type PL2	Medium_Box
Packaging Volume PL1	0,000186
Packaging Volume PL2	0,0023625
Packaging Weight PL1	0,162
Packaging Weight PL2	3,348
Packaging Width PL1	50
Packaging Width PL2	105

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E
communications@georgfischer.
com