


Uponor Vario actuator NC FT 24V 1W IP54

1141677

- Vario M, S manifold actuator
- first open function,
- height: 61 mm + adaptor ring
- stroke length: 5mm
- connection cable: 2x 0.75mm²x1m



Application information Uponor Vario actuator NC

Specification


- Components made of brass, nickel-plated brass, steel, and engineered plastics
- Eurocone, threaded, and flat-sealing connections
- Compatible with Vario B, C, S, M, PLUS, and MAGNA manifolds
- Includes valves, flowmeters, air vents, actuators, and adapters
- Designed for heating and cooling applications

Application

- Completion and extension of Vario manifold installations
- Flow regulation, balancing, and shut-off
- Connection of PEX, MLCP, and composite pipes
- Integration of actuators, sensors, and control units
- Commissioning, maintenance, and system optimization

Uponor Vario actuator NC FT 24V 1W IP54

1141677



Status

Item Available From date

2024-01-01

Product code

Item no EAN	6414900383776
Item no GF	35001141677
Item no GTIN	06414900383776
Item no LVI	2022271
Item no NRF	8361387
Item no RSK	2973122
Item no VVS	466235424

Dimensions

Item Unit Height	83
Item Unit Length	50
Item Unit Weight	0,12
Item Unit Width	30
Item_UOM	pce

Measurements

Outer Diameter_do	50
Z Measurement h	83

Packaging

Packaging GTIN PL1	06414900383837
Packaging GTIN PL2	06414900385367
Packaging GTIN PL4	06414900385398
Packaging Height PL1	170
Packaging Height PL2	255
Packaging Height PL4	1000
Packaging Length PL1	55
Packaging Length PL2	590

Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL2	100
Packaging Quantity PL4	1200
Packaging Type PL1	Base_Box
Packaging Type PL2	Medium_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00042075
Packaging Volume PL2	0,0556665
Packaging Volume PL4	0,96
Packaging Weight PL1	0,13
Packaging Weight PL2	14
Packaging Weight PL4	205
Packaging Width PL1	45
Packaging Width PL2	370
Packaging Width PL4	800

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com