Product data sheet



GF Uponor Smatrix Wave thermostat D+RH T-267

1144106

- Measures and displays the room temperature and relative humidity
- Compatible with controllers Smatrix Wave Pulse (X-265) and Smatrix Wave (X-165)
- Color: white RAL9016

Functions:
- Capacitive keys on the front
- Heating or cooling demand indication
- RH measured value
- Comfort / ECO indication
- ECO setback modification
- Cooling allowed function (room by room)
- Displays celsius or fahrenheit
- Operating modes: room temperature (RT), internal with floor max/min (RFT), remote sensor (RS), remote outdoor (RO)
- Low battery indication
- Room Temperature calibration
- Optional: floor, remote or outdoor sensor can be connected

Consisting of:
- Uponor Smatrix Wave thermostat D+RH T-267
- 2x AAA batteries
- Thermometer stand
- Mounting material



Application information GF Uponor Smatrix Wave thermostat D+RH T-267

Specification

- modular system includes controller, expansion module, com module with app for mobile devices, relay modules, thermostats and sensors
- wireless connections with Smatrix Wave thermostats
- up tp 8 room thermostats and 10 actuators (24V) per controller
- up to 14 room thermostats and 16 actuators (24V) per controller with expansion module
- up to 4 controllers in one system, wireless connected
- pump and boiler relays (output) with every controller
- 4 outputs in total for systems with relay module M-161, configurable via app
- heating/cooling switch input
- heating/cooling change with thermostat T-267
- relative humidity control with thermostats and sensors
- combines underfloor heating/cooling and ceiling cooling control
- app for mobile devices with installation wizard and intuitive user interface
- on-site access with Bluetooth BLE for commissioning and service
- generating installation configurations for repeated use in the app
- remote access via app for internet connected systems
- Smatrix AI for energy savings in installations with heat pumps
- schedule settings, via app or programmable thermostat T-168
- comfort settings
- shut-off function for the seasonal transitional period
- valve and pump exercise
- fast automatic software updates
- supply diagnostics for internet connected systems
- color LEDs on controller providing status information
- operating voltage of controller 230V
- low voltage actuators: 24VAC /0.2A (0.4A peak)

Application

- wireless room temperature control for radiant heating and cooling
- set point range: +5°C ... +35°C

Certification

- CE, UKCA

GF Uponor Smatrix Wave thermostat D+RH T-267

1144106



Status

Item Available From date	2025-04-01

Product code

Item no EAN	6414900327756
Item no GF	35001144106
Item no GTIN	06414900327756
Item no LVI	2022331
Item no NRF	1430886
Item no RSK	2973229
Item no VVS	466251026

Dimensions

Item Unit Height	21
Item Unit Length	86
Item Unit Weight	0,087
Item Unit Width	86
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414900508797
Packaging GTIN PL3	06414900447447
Packaging GTIN PL4	06414900447478
Packaging Height PL1	40
Packaging Height PL3	300
Packaging Height PL4	1050
Packaging Length PL1	100
Packaging Length PL3	400
Packaging Length PL4	1200

Packaging Quantity PL1	1
Packaging Quantity PL3	75
Packaging Quantity PL4	1800
Packaging Type PL1	Base_Box
Packaging Type PL3	Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00036
Packaging Volume PL3	0,036
Packaging Volume PL4	1,008
Packaging Weight PL1	0,139
Packaging Weight PL3	11,02
Packaging Weight PL4	284
Packaging Width PL1	90
Packaging Width PL3	300
Packaging Width PL4	800

Documents

Page with all documents

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E communications@georgfischer.com

www.uponor.com

+GF+