


## GF Silenta premium elbow 45deg 160mm

1146320

- Light gray, PP-material with inorganic filler, according to EN 1451



### Application information GF Silenta premium elbow 45deg

#### Specification

- Three-layer polypropylene pipe system manufactured according to EN 1451
- Sound-insulated construction with enhanced mechanical strength
- Pipe diameter range: DN 58 to DN 200
- High chemical and temperature resistance
- Complete system including pipes, fittings and accessories

#### Application

- Residential buildings and apartment complexes
- Hotels, hospitals, schools and office buildings
- Sustainable and green buildings
- Industrial facilities (short and long-term wastewater use)
- Domestic sewage systems
- Wastewater from kitchens, bathrooms, laundry rooms and sanitary areas

## GF Silenta premium elbow 45deg 160mm

1146320



### Status

Item Available From date 2026-02-01

### Product code

Item no EAN	8698652133553
Item no GF	4501116030221
Item no GTIN	08698652133553
Item no VVS	186833018

### Dimensions

Item Unit Height	265
Item Unit Length	188
Item Unit Weight	1,21
Item Unit Width	235
Item_UOM	pce

### Packaging

Packaging GTIN PL1	06414900602044
Packaging GTIN PL2	06414900341479
Packaging GTIN PL4	06414900214506
Packaging Height PL1	265
Packaging Height PL2	360
Packaging Height PL4	1200
Packaging Length PL1	188
Packaging Length PL2	590
Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL2	8
Packaging Quantity PL4	96
Packaging Type PL1	Piece
Packaging Type PL2	Medium_Box

Packaging Type PL4	Pallet
Packaging Volume PL1	0,0117077
Packaging Volume PL2	0,082836
Packaging Volume PL4	1,152
Packaging Weight PL1	1,21
Packaging Weight PL2	9,68
Packaging Weight PL4	141,16
Packaging Width PL1	235
Packaging Width PL2	390
Packaging Width PL4	800

### Measurements

Z Measurement e	5,3
-----------------	-----

### Documents

Page with all documents



#### Uponor Corporation

Ilmalantori 4  
00240, Helsinki  
Finland

T +358 (0)20 129 211

[www.uponor.com](http://www.uponor.com)