


## GF Silenta 3A pipe with single socket 40x150mm

**1146568**

- Light blue, three-layer, PP-material with inorganic filler, according to EN 1451



### Application information GF Silenta 3A pipe with single socket

#### Specification

- Three-layer polypropylene soil and wastewater pipe system
- Compliant with DIN EN 1451, DIN 4109 and DIN 4102
- Designed for non-pressurized domestic drainage
- Pipe diameter range: DN 32 to DN 200
- Complete system including pipes, fittings and accessories

#### Application

- Residential buildings and apartment complexes
- Schools, libraries, hospitals and hotels
- Office buildings, administrative centers and conference facilities
- Sustainable and green building projects
- Industrial facilities, suitable for both short- and long-term wastewater applications

## GF Silenta 3A pipe with single socket 40x150mm

1146568



### Status

Item Available From date

2026-02-01

### Product code

Item no EAN	8698652117812
Item no GF	4604004000121
Item no GTIN	08698652117812
Item no NOBB	60823802
Item no NRF	1486133
Item no RSK	2749174

### Dimensions

Item Unit Height	40
Item Unit Length	150
Item Unit Weight	0,073
Item Unit Width	40
Item_UOM	pce

### Measurements

LENGTH_L	150
Wall thickness_s	16
Z Measurement e	1,8

### Packaging

Packaging GTIN PL1	06414900554961
Packaging GTIN PL2	06414900565677
Packaging GTIN PL4	06414900565684
Packaging Height PL1	40
Packaging Height PL2	400
Packaging Height PL4	944
Packaging Length PL1	150
Packaging Length PL2	800

Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL2	300
Packaging Quantity PL4	1200
Packaging Type PL1	Piece
Packaging Type PL2	Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00024
Packaging Volume PL2	0,192
Packaging Volume PL4	0,90624
Packaging Weight PL1	0,073
Packaging Weight PL2	23,46
Packaging Weight PL4	118,84
Packaging Width PL1	40
Packaging Width PL2	600
Packaging Width PL4	800

## Documents

Page with all documents



### Uponor Corporation

Ilmalantori 4  
00240, Helsinki  
Finland

T +358 (0)20 129 211

[www.uponor.com](http://www.uponor.com)