
Product data sheet



GF JRG adjustable socket DN20

1149454

- Made of gunmetal (lead-free)
- Temperature: max. 90°C
- Nominal pressure: PN16
- Connection: female thread



Application information GF JRG adjustable socket

Specification


- Wide product range
- Gunmetal body

Application

Potable water installations

GF JRG adjustable socket DN20

1149454



Product code

Item no EAN	7613263016676
Item no GF	350667401
Item no GTIN	07613263016676
Item no RSK	4883221

Dimensions

Item Unit Height	36
Item Unit Length	78
Item Unit Weight	0,446
Item Unit Width	65
Item_UOM	pce

Measurements

LENGTH_L	64
Z Measurement d	20
Z Measurement d2	36
Z Measurement h	61
Z	17

Packaging

Packaging GTIN PL1	06414900057615
Packaging Height PL1	60
Packaging Length PL1	120
Packaging Material (number) PL1	04
Packaging Material PL1	plastic film / film plastico
Packaging Material (short) PL1	PELD
Packaging Quantity PL1	1
Packaging Type PL1	Pouch

Packaging Volume PL1	0,000648
Packaging Weight PL1	0,449
Packaging Width PL1	90

Technical data

Recycling Text Block PL1	plastic film / film plastico

Documents

Page with all documents

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E communications@georgfischer.com

www.uponor.com

+GF+