


GF JRGUMAT thermostatic mixing valve 3400 40°C DN50

1149459

- Temperature: max. 90°C
- Nominal pressure: PN10
- Factory setting: 40°C (30-45°C)
- Material: gunmetal
- Connection: male thread



Application information GF JRGUMAT thermostatic mixing valve 3400 40°C

Specification


- Dimensionen: DN15 – DN80
- Temperaturbereich: 20-80°C, e.g. 25, 40, 55 and 70°C)

Application

- Potable water systems with requirement for constant mixed water temperature
- Central and decentralized hot water mixing for single and multifamily homes, hospitality buildings and sports facilities
- Excess temperature protection in systems using alternative forms of energy such as solar systems

GF JRGUMAT thermostatic mixing valve 3400 40°C DN50

1149459



Measurements

Cylindric thread G2	2 3/4
Cylindric thread G3	3/4
LENGTH_L	180
Length (l1)	70
Length (l2)	110
Z Measurement d	50
Z Measurement h1	60
Z Measurement h2	85
Z Measurement h3	70

Product code

Item no EAN	7613263101440
Item no GF	350760012
Item no GTIN	07613263101440
Item no RSK	4927925
Item no VVS	723481012

Dimensions

Item Unit Height	154.5
Item Unit Length	180
Item Unit Weight	3,51
Item Unit Width	94.5
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414900057646
Packaging Height PL1	126
Packaging Length PL1	290
Packaging Quantity PL1	1
Packaging Type PL1	Base_Box

Packaging Volume PL1	0,00807534
Packaging Weight PL1	3,82
Packaging Width PL1	221

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E
communications@georgfischer.
com