




GF JRGUMAT thermostatic mixing valve 3400, 40°C DN50

1149459

- Made of gunmetal (lead-free)
- Temperature: max. 90°C
- Nominal pressure: PN10
- Factory setting: 40°C (30-45°C)
- Connection: male thread



Application information GF JRGUMAT thermostatic mixing valve 3400, 40°C

Specification


- Dimensionen: DN15 – DN80
- Temperaturbereich: 20-80°C, e.g. 25, 40, 55 and 70°C)

Application

- Potable water systems with requirement for constant mixed water temperature
- Central and decentralized hot water mixing for single and multifamily homes, hospitality buildings and sports facilities
- Excess temperature protection in systems using alternative forms of energy such as solar systems

GF JRGUMAT thermostatic mixing valve 3400, 40°C DN50

1149459



Product code

Item no EAN	7613263101440
Item no GF	350760012
Item no GTIN	07613263101440
Item no RSK	4927925
Item no VVS	723481012

Dimensions

Item Unit Height	154.5
Item Unit Length	180
Item Unit Weight	3,51
Item Unit Width	94.5
Item_UOM	pce

Measurements

LENGTH_L	180
Length (l1)	70
Length (l2)	110
Z Measurement d	50
Z Measurement d2	G2 3/4"
Z Measurement d3	G3/4"
Z Measurement d3	G3/4"
Z Measurement h1	60
Z Measurement h2	85
Z Measurement h3	70

Packaging

Packaging GTIN PL1	06414900057646
Packaging Height PL1	126

Packaging Length PL1	290
Packaging Quantity PL1	1
Packaging Type PL1	Base_Box
Packaging Volume PL1	0,00807534
Packaging Weight PL1	3,82
Packaging Width PL1	221

Documents

Page with all documents 

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E communications@georgfischer.com

www.uponor.com

