


GF JRGUMAT thermostatic mixing valve 3400 55°C DN50**1149460**

- Temperature: max. 90°C
- Nominal pressure: PN10
- Factory setting: 55°C (45-65°C)
- Material: gunmetal
- Connection: male thread

**Application information GF JRGUMAT thermostatic mixing valve 3400 55°C****Specification**

- Dimension range DN15 – DN80
- Different temperature ranges (20-80°C) and factory settings (e.g. 25, 40, 55 and 70°C)

Application

- Potable water systems with requirements for constant mixed water temperature
- Central and decentralized hot water mixing for single- and multi-family homes, hospitality buildings and sports facilities
- Excess-temperature protection in systems using alternative forms of energy such as solar systems

GF JRGUMAT thermostatic mixing valve 3400 55°C DN50

1149460



Measurements

Cylindric thread G2	2 3/4
Cylindric thread G3	3/4
LENGTH_L	180
Length (l1)	70
Length (l2)	110
Z Measurement d	50
Z Measurement h1	60
Z Measurement h2	85
Z Measurement h3	70

Product code

Item no EAN	7613263101747
Item no GF	350760013
Item no GTIN	07613263101747
Item no RSK	4927927

Dimensions

Item Unit Height	154.5
Item Unit Length	180
Item Unit Weight	3,51
Item Unit Width	94.5
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414900057653
Packaging Height PL1	123
Packaging Length PL1	290
Packaging Quantity PL1	1
Packaging Type PL1	Base_Box
Packaging Volume PL1	0,00788307

Packaging Weight PL1	3,82
Packaging Width PL1	221

Documents

Page with all documents 

Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E
communications@georgfischer.
com