


GF JRGUMAT thermostatic mixing valve 3400 40°C DN40

1149472

- Temperature: max. 90°C
- Nominal pressure: PN10
- Factory setting: 40°C (30-45°C)
- Material: gunmetal
- Connection: male thread



Application information GF JRGUMAT thermostatic mixing valve 3400 40°C

Specification


- Dimension range DN15 – DN80
- Different temperature ranges (20-80°C) and factory settings (e.g. 25, 40, 55 and 70°C)

Application

- Potable water systems with requirements for constant mixed water temperature
- Central and decentralized hot water mixing for single- and multi-family homes, hospitality buildings and sports facilities
- Excess-temperature protection in systems using alternative forms of energy such as solar systems

GF JRGUMAT thermostatic mixing valve 3400 40°C DN40

1149472



Measurements

Cylindric thread G2	2 1/4
Cylindric thread G3	3/4
LENGTH_L	150
Length (l1)	58
Length (l2)	92
Z Measurement d	40
Z Measurement h1	50
Z Measurement h2	77
Z Measurement h3	58

Product code

Item no EAN	7613263102737
Item no GF	350760112
Item no GTIN	07613263102737
Item no RSK	4927921
Item no VVS	723481011

Dimensions

Item Unit Height	135
Item Unit Length	150
Item Unit Weight	2,14
Item Unit Width	75.5
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414900057745
Packaging Height PL1	105
Packaging Length PL1	250
Packaging Quantity PL1	1
Packaging Type PL1	Base_Box

Packaging Volume PL1	0,005145
Packaging Weight PL1	2,34
Packaging Width PL1	196

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E
communications@georgfischer.
com