Product data sheet



GF JRGUMAT thermostatic mixing valve 3400, 40°C DN32

1149482

- Made of gunmetal (lead-free)
- Temperature: max. 90°C
- Nominal pressure: PN10
- Factory setting: 40°C (30-45°C)
- Connection: male thread



Application information GF JRGUMAT thermostatic mixing valve 3400, 40°C

Specification

- Dimensionen: DN15 – DN80
- Temperaturbereich: 20-80°C, e.g. 25, 40, 55 and 70°C)

Application

- Potable water systems with requirement for constant mixed water temperature
- Central and decentralized hot water mixing for single and multifamily homes, hospitality buildings and sports facilities
- Excess temperature protection in systems using alternative forms of energy such as solar systems

GF JRGUMAT thermostatic mixing valve 3400, 40°C DN32

1149482



Product code

Item no EAN	7613263102690
Item no GF	350760212
Item no GTIN	07613263102690
Item no RSK	4927917
Item no VVS	723481010

Dimensions

Item Unit Height	127
Item Unit Length	130
Item Unit Weight	1,63
Item Unit Width	60
Item_UOM	pce

Measurements

LENGTH_L	130
Length (l1)	52
Length (l2)	78
Z Measurement d2	G2"
Z Measurement D3	G3/4"
Z Measurement h1	41
Z Measurement h2	75
Z Measurement h3	52

Packaging

Packaging GTIN PL1	06414900169318
Packaging Height PL1	102
Packaging Length PL1	220
Packaging Quantity PL1	1

Packaging Type PL1	Base_Box
Packaging Volume PL1	0,00406164
Packaging Weight PL1	1,81
Packaging Width PL1	181

Documents

Page with all documents

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E communications@georgfischer.com

www.uponor.com

+GF+