


**GF JRGUMAT thermostatic mixing valve 3400 55°C DN32****1149483**

- Temperature: max. 90°C
- Nominal pressure: PN10
- Factory setting: 55°C (45-65°C)
- Material: gunmetal
- Connection: male thread

**Application information GF JRGUMAT thermostatic mixing valve 3400 55°C****Specification**

- Dimension range DN15 – DN80
- Different temperature ranges (20-80°C) and factory settings (e.g. 25, 40, 55 and 70°C)

**Application**

- Potable water systems with requirements for constant mixed water temperature
- Central and decentralized hot water mixing for single- and multi-family homes, hospitality buildings and sports facilities
- Excess-temperature protection in systems using alternative forms of energy such as solar systems

## GF JRGUMAT thermostatic mixing valve 3400 55°C DN32

1149483



### Measurements

Cylindric thread G2	2
Cylindric thread G3	3/4
LENGTH_L	130
Length (l1)	52
Length (l2)	78
Z Measurement d	32
Z Measurement h1	41
Z Measurement h2	75
Z Measurement h3	52

### Product code

Item no EAN	7613263100160
Item no GF	350760213
Item no GTIN	07613263100160
Item no RSK	4927919

### Dimensions

Item Unit Height	127
Item Unit Length	130
Item Unit Weight	1,59
Item Unit Width	60
Item_UOM	pce

### Packaging

Packaging GTIN PL1	06414900169325
Packaging Height PL1	102
Packaging Length PL1	220
Packaging Quantity PL1	1
Packaging Type PL1	Base_Box
Packaging Volume PL1	0,00406164

Packaging Weight PL1	1,81
Packaging Width PL1	181

## Documents

Page with all documents 

### Uponor Corporation

Ilmalantori 4  
00240, Helsinki  
Finland

T +358 (0)20 129 211  
E  
communications@georgfischer.  
com