




GF JRGUMAT thermostatic mixing valve 3400, 55°C DN25

1149493

- Made of gunmetal (lead-free)
- Temperature: max. 90°C
- Nominal pressure: PN10
- Factory setting: 55°C (45-65°C)
- Connection: male thread



Application information GF JRGUMAT thermostatic mixing valve 3400, 55°C

Specification


- Dimensionen: DN15 – DN80
- Temperaturbereich: 20-80°C, e.g. 25, 40, 55 and 70°C)

Application

- Potable water systems with requirement for constant mixed water temperature
- Central and decentralized hot water mixing for single and multifamily homes, hospitality buildings and sports facilities
- Excess temperature protection in systems using alternative forms of energy such as solar systems

GF JRGUMAT thermostatic mixing valve 3400, 55°C DN25

1149493



Product code

Item no EAN	7613263098948
Item no GF	350760313
Item no GTIN	07613263098948
Item no RSK	4927915

Dimensions

Item Unit Height	94
Item Unit Length	110
Item Unit Weight	0,91
Item Unit Width	48
Item_UOM	pce

Measurements

LENGTH_L	110
Length (l1)	43
Length (l2)	67
Z Measurement d2	G1 1/2"
Z Measurement d3	G3/4"
Z Measurement d3	G3/4"
Z Measurement h1	36
Z Measurement h2	51
Z Measurement h3	43

Packaging

Packaging GTIN PL1	06414900169417
Packaging Height PL1	91
Packaging Length PL1	190
Packaging Quantity PL1	1

Packaging Type PL1	Base_Box
Packaging Volume PL1	0,00252434
Packaging Weight PL1	1
Packaging Width PL1	146

Documents

Page with all documents 

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E communications@georgfischer.com

www.uponor.com

