


GF JRGUMAT thermostatic mixing valve 3400 40°C DN20

1149503

- Temperature: max. 90°C
- Nominal pressure: PN10
- Factory setting: 40°C (30-45°C)
- Material: gunmetal
- Connection: male thread



Application information GF JRGUMAT thermostatic mixing valve 3400 40°C

Specification


- Dimensionen: DN15 – DN80
- Temperaturbereich: 20-80°C, e.g. 25, 40, 55 and 70°C)

Application

- Potable water systems with requirement for constant mixed water temperature
- Central and decentralized hot water mixing for single and multifamily homes, hospitality buildings and sports facilities
- Excess temperature protection in systems using alternative forms of energy such as solar systems

GF JRGUMAT thermostatic mixing valve 3400 40°C DN20

1149503



Measurements

Cylindric thread G2	1 1/4
Cylindric thread G3	1/2
LENGTH_L	100
Length (l1)	40
Length (l2)	60
Z Measurement d	20
Z Measurement h1	32
Z Measurement h2	49
Z Measurement h3	40

Product code

Item no EAN	7613263098986
Item no GF	350760412
Item no GTIN	07613263098986
Item no RSK	4927909
Item no VVS	723481006

Dimensions

Item Unit Height	89
Item Unit Length	100
Item Unit Weight	0,67
Item Unit Width	42
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414900169493
Packaging Height PL1	81
Packaging Length PL1	190
Packaging Quantity PL1	1
Packaging Type PL1	Base_Box

Packaging Volume PL1	0,00232389
Packaging Weight PL1	0,8
Packaging Width PL1	151

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E
communications@georgfischer.
com