Product data sheet



GF JRGUMAT thermostatic mixing valve 3400, 40°C DN15

1149509

- Made of gunmetal (lead-free)
- Temperature: max. 90°C
- Nominal pressure: PN10
- Factory setting: 40°C (30-45°C)
- Connection: male thread



Application information GF JRGUMAT thermostatic mixing valve 3400, 40°C

Specification

- Dimensionen: DN15 – DN80
- Temperaturbereich: 20-80°C, e.g. 25, 40, 55 and 70°C)

Application

- Potable water systems with requirement for constant mixed water temperature
- Central and decentralized hot water mixing for single and multifamily homes, hospitality buildings and sports facilities
- Excess temperature protection in systems using alternative forms of energy such as solar systems

GF JRGUMAT thermostatic mixing valve 3400, 40°C DN15

1149509



Product code

Item no EAN	7613263099020
Item no GF	350760512
Item no GTIN	07613263099020
Item no RSK	4927905
Item no VVS	723481004

Dimensions

Item Unit Height	82
Item Unit Length	90
Item Unit Weight	0,53
Item Unit Width	38
Item_UOM	pce

Measurements

LENGTH_L	90
Length (l1)	35
Length (l2)	55
Z Measurement d2	G1 1/8"
Z Measurement D3	G1/2"
Z Measurement h2	47
Z Measurement h3	35

Packaging

Packaging GTIN PL1	06414900169547
Packaging Height PL1	75
Packaging Length PL1	170
Packaging Quantity PL1	1
Packaging Type PL1	Base_Box

Packaging Volume PL1	0,0018105
Packaging Weight PL1	0,64
Packaging Width PL1	142

Documents

Page with all documents

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E communications@georgfischer.com

www.uponor.com

+GF+