


GF JRGUMAT thermostatic mixing valve 3400 55°C DN15**1149510**

- Temperature: max. 90°C
- Nominal pressure: PN10
- Factory setting: 55°C (45-65°C)
- Material: gunmetal
- Connection: male thread

**Application information GF JRGUMAT thermostatic mixing valve 3400 55°C****Specification**

- Dimension range DN15 – DN80
- Different temperature ranges (20-80°C) and factory settings (e.g. 25, 40, 55 and 70°C)

Application

- Potable water systems with requirements for constant mixed water temperature
- Central and decentralized hot water mixing for single- and multi-family homes, hospitality buildings and sports facilities
- Excess-temperature protection in systems using alternative forms of energy such as solar systems

GF JRGUMAT thermostatic mixing valve 3400 55°C DN15

1149510



Measurements

Cylindric thread G2	1 1/8
LENGTH_L	90
Length (l1)	35
Length (l2)	55
Z Measurement d	15
Z Measurement h2	47
Z Measurement h3	35

Product code

Item no EAN	7613263099037
Item no GF	350760513
Item no GTIN	07613263099037
Item no RSK	4927907

Dimensions

Item Unit Height	82
Item Unit Length	90
Item Unit Weight	0,53
Item Unit Width	38
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414900169554
Packaging Height PL1	75
Packaging Length PL1	170
Packaging Quantity PL1	1
Packaging Type PL1	Base_Box
Packaging Volume PL1	0,0018105
Packaging Weight PL1	0,64
Packaging Width PL1	142

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E
communications@georgfischer.
com