Product data sheet



GF JRGUMAT thermostatic mixing valve 3410, 40°C DN65

1149521

- Made of gunmetal (lead-free)
- Temperature: max. 90°C
- Nominal pressure: PN10
- Factory setting: 40°C (30-45°C)
- Connection: flange



Application information GF JRGUMAT thermostatic mixing valve 3410, 40°C

Specification

- Dimensionen: DN15 – DN80
- Temperaturbereich: 20-80°C, e.g. 25, 40, 55 and 70°C)

Application

- Potable water systems with requirement for constant mixed water temperature
- Central and decentralized hot water mixing for single and multifamily homes, hospitality buildings and sports facilities
- Excess temperature protection in systems using alternative forms of energy such as solar systems

GF JRGUMAT thermostatic mixing valve 3410, 40°C DN65

1149521



Product code

Item no EAN	7613263101471
Item no GF	350767215
Item no GTIN	07613263101471
Item no RSK	4927897

Dimensions

Item Unit Height	266.5
Item Unit Length	290
Item Unit Weight	22,5
Item Unit Width	185
Item_UOM	pce

Measurements

Length (l1)	145
Length (l2)	290
Length (l3)	112
Z Measurement d1	65
Z Measurement d2	G1 1/2"
Z Measurement D3	185
Z Measurement h1	82
Z Measurement h2	121

Packaging

Packaging GTIN PL1	06414900169646
Packaging Height PL1	220
Packaging Length PL1	395
Packaging Quantity PL1	1
Packaging Type PL1	Base_Box

Packaging Volume PL1	0,0291115
Packaging Weight PL1	22,85
Packaging Width PL1	335

Documents

Page with all documents

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E communications@georgfischer.com

www.uponor.com

+GF+