


GF JRGUMAT thermostatic mixing valve 3410 55°C DN65

1149522

- Temperature: max. 90°C
- Nominal pressure: PN10
- Factory setting: 55°C (45-65°C)
- Material: gunmetal
- Connection: flange



Application information GF JRGUMAT thermostatic mixing valve 3410 55°C

Specification

- Dimension range DN15 – DN80
- Different temperature ranges (20-80°C) and factory settings (e.g. 25, 40, 55 and 70°C)

Application

- Potable water systems with requirements for constant mixed water temperature
- Central and decentralized hot water mixing for single- and multi-family homes, hospitality buildings and sports facilities
- Excess-temperature protection in systems using alternative forms of energy such as solar systems

GF JRGUMAT thermostatic mixing valve 3410 55°C DN65

1149522



Measurements

Cylindric thread G2	1 1/2
Inner_diameter_di	65
Length (l1)	145
Length (l2)	290
Length (l3)	112
Z Measurement d	65
Z Measurement d1	65
Z Measurement d3	185
Z Measurement d3	185
Z Measurement h1	82
Z Measurement h2	121

Product code

Item no EAN	7613263101778
Item no GF	350767216
Item no GTIN	07613263101778
Item no RSK	4927899

Dimensions

Item Unit Height	266.5
Item Unit Length	290
Item Unit Weight	22,5
Item Unit Width	185
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414900169653
Packaging Height PL1	220
Packaging Length PL1	395
Packaging Quantity PL1	1

Packaging Type PL1	Base_Box
Packaging Volume PL1	0,0291115
Packaging Weight PL1	22,8499709871702
Packaging Width PL1	335

Documents

Page with all documents 

Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E
communications@georgfischer.
com