


## GF JRGUMAT thermostatic mixing valve 3410 55°C DN80

**1149531**

- Temperature: max. 90°C
- Nominal pressure: PN10
- Factory setting: 55°C (45-65°C)
- Material: gunmetal
- Connection: flange



### Application information GF JRGUMAT thermostatic mixing valve 3410 55°C

#### Specification

- Dimension range DN15 – DN80
- Different temperature ranges (20-80°C) and factory settings (e.g. 25, 40, 55 and 70°C)

#### Application

- Potable water systems with requirements for constant mixed water temperature
- Central and decentralized hot water mixing for single- and multi-family homes, hospitality buildings and sports facilities
- Excess-temperature protection in systems using alternative forms of energy such as solar systems

## GF JRGUMAT thermostatic mixing valve 3410 55°C DN80

1149531



### Measurements

Inner_diameter_di	80
Length (l1)	155
Length (l2)	310
Length (l3)	124
Z Measurement h1	92
Z Measurement h2	127

### Product code

Item no EAN	7613263101808
Item no GF	350767416
Item no GTIN	07613263101808
Item no RSK	4927903

### Dimensions

Item Unit Height	282.5
Item Unit Length	310
Item Unit Weight	27,5
Item Unit Width	200
Item_UOM	pce

### Packaging

Packaging GTIN PL1	06414900169714
Packaging Height PL1	230
Packaging Length PL1	420
Packaging Quantity PL1	1
Packaging Type PL1	Base_Box
Packaging Volume PL1	0,034293
Packaging Weight PL1	27,8911001199972
Packaging Width PL1	355

## Documents

Page with all documents



### Uponor Corporation

Ilmalantori 4  
00240, Helsinki  
Finland

T +358 (0)20 129 211

[www.uponor.com](http://www.uponor.com)