
Product data sheet



GF JRGUTHERM balancing valve DN15

1149540

- Made of gunmetal (lead-free)
- factory setting 57°C (adjustable 36 - 63°C), including insulation shell
- Temperature: max. 90°C
- Nominal pressure: PN10
- Connection: screw connection



Application information GF JRGUTHERM balancing valve

Specification


- Dimension range DN15 & DN20
- Factory setting: 57°C, adjustable 36-63°C

Application

- Hot water circulation return line (PWH-C)

GF JRGUTHERM balancing valve DN15

1149540



Product code

Item no EAN	7613263013163
Item no GF	350831401
Item no GTIN	07613263013163
Item no LVI	4013720
Item no RSK	4883212

Dimensions

Item Unit Height	75
Item Unit Length	195
Item Unit Weight	0,5
Item Unit Width	110
Item_UOM	pce

Measurements

LENGTH_L	60
Length (l1)	194
Length (l2)	38
Length (l3)	70
Z Measurement b1	37
Z Measurement d1	G3/4"
Z Measurement h	64

Packaging

Packaging GTIN PL1	06414900169783
Packaging Height PL1	75
Packaging Length PL1	205
Packaging Quantity PL1	1
Packaging Type PL1	Base_Box

Packaging Volume PL1	0,00169125
Packaging Weight PL1	0,5523
Packaging Width PL1	110

Documents

Page with all documents

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E communications@georgfischer.com

www.uponor.com

+GF+