
Product data sheet



GF JRGUTHERM balancing valve DN20

1149543

- Made of gunmetal (lead-free)
- factory setting 57°C (adjustable 36 - 63°C), including insulation shell
- Temperature: max. 90°C
- Nominal pressure: PN10
- Connection: screw connection



Application information GF JRGUTHERM balancing valve

Specification


- Dimension range DN15 & DN20
- Factory setting: 57°C, adjustable 36-63°C

Application

- Hot water circulation return line (PWH-C)

GF JRGUTHERM balancing valve DN20

1149543



Product code

Item no EAN	7613263013156
Item no GF	350831501
Item no GTIN	07613263013156
Item no RSK	4883213

Dimensions

Item Unit Height	75
Item Unit Length	190
Item Unit Weight	0,519
Item Unit Width	110
Item_UOM	pce

Measurements

LENGTH_L	60
Length (l1)	194
Length (l2)	38
Length (l3)	70
Z Measurement b1	37
Z Measurement d1	G1"
Z Measurement h	64

Packaging

Packaging GTIN PL1	06414900169813
Packaging Height PL1	75
Packaging Length PL1	195
Packaging Quantity PL1	1
Packaging Type PL1	Base_Box
Packaging Volume PL1	0,00160875

Packaging Weight PL1	0,619
Packaging Width PL1	110

Documents

Page with all documents

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E communications@georgfischer.com

www.uponor.com

+GF+