Product data sheet



GF HT-PP pipe with single socket S16 110-2000

1150106

- Gray, monolayer, PP-material, according to EN 1451



Application information GF HT-PP pipe with single socket S16

Specification

- The system is made from monolayer polypropylene (PP) to ensure reliable performance in standard drainage applications.
- It is designed for non-pressurized soil and wastewater drainage in residential and commercial buildings.
- The system is fully compliant with EN 1451-1 for plastic soil and waste discharge and EN 13501 for fire classification.
- It achieves fire performance rating E according to EN 13501.
- The pipes are suitable for short-term exposure to high-temperature wastewater.
- The material provides high resistance to chemicals commonly found in domestic and commercial wastewater.
- The push-fit socket design with integrated sealing rings ensures quick installation and leak-tight connections.
- The system is available in nominal diameters ranging from DN 32 to DN 200.

Application

- Residential buildings
- Office buildings and conference facilities
- Schools, libraries, hospitals, and hotels
- Underground and above-ground house drainage
- Sustainable / green building projects
- Industrial facilities (short- and long-term use)
- Wastewater from kitchens, bathrooms, and household appliances (e.g. washing machines, dishwashers)

GF HT-PP pipe with single socket S16 110-2000

1150106



Status

Item Available From date	2026-02-01

Product code

Item no EAN	8698652092683
Item no GF	4801011025421
Item no GTIN	08698652092683

Dimensions

Item Unit Height	110
Item Unit Length	2000
Item Unit Weight	2,398
Item Unit Width	110
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414900600156
Packaging GTIN PL2	06414900173193
Packaging Height PL1	110
Packaging Height PL2	250
Packaging Length PL1	2000
Packaging Length PL2	2000
Packaging Quantity PL1	1
Packaging Quantity PL2	4
Packaging Type PL1	Piece
Packaging Type PL2	Bag
Packaging Volume PL1	0,0242
Packaging Volume PL2	0,125
Packaging Weight PL1	2,398

Packaging Weight PL2	9,592
Packaging Width PL1	110
Packaging Width PL2	250

Measurements

Wall thickness_s	16
Z Measurement d	129,3
Z Measurement d1	110
Z Measurement e	3,4
Z Measurement L	2000
Z Measurement L1	65
Z Measurement LB	2065

Documents

Page with all documents

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E communications@georgfischer.com

www.uponor.com

+GF+