

GF HT-PP pipe with single socket S20 125x3000mm

1150112

- Gray, monolayer, PP-material, according to EN 1451. The S class is S20.



Application information GF HT-PP pipe with single socket

Specification

- The system is made from monolayer polypropylene (PP) to ensure reliable performance in standard drainage applications.
- It is designed for non-pressurized soil and wastewater drainage in residential and commercial buildings.
- The system is fully compliant with EN 1451-1 for plastic soil and waste discharge and EN 13501 for fire classification.
- It achieves fire performance rating E according to EN 13501.
- The pipes are suitable for short-term exposure to high-temperature wastewater.
- The material provides high resistance to chemicals commonly found in domestic and commercial wastewater.
- The push-fit socket design with integrated sealing rings ensures quick installation and leak-tight connections.
- The system is available in nominal diameters ranging from DN 32 to DN 200.

Application

- Residential buildings
- Office buildings and conference facilities
- Schools, libraries, hospitals, and hotels
- Underground and above-ground house drainage
- Sustainable / green building projects
- Industrial facilities (short- and long-term use)
- Wastewater from kitchens, bathrooms, and household appliances (e.g. washing machines, dishwashers)

GF HT-PP pipe with single socket S20 125x3000mm

1150112



Status

Item Available From date 2026-02-01

Product code

Item no EAN	8698652031590
Item no GF	4801012505521
Item no GTIN	08698652031590
Item no VVS	186028300

Dimensions

Item Unit Height	125
Item Unit Length	3000
Item Unit Weight	4,159
Item Unit Width	125
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414900600279
Packaging GTIN PL2	06414900173254
Packaging Height PL1	125
Packaging Height PL2	275
Packaging Length PL1	3000
Packaging Length PL2	3000
Packaging Quantity PL1	1
Packaging Quantity PL2	4
Packaging Type PL1	Piece
Packaging Type PL2	Bag
Packaging Volume PL1	0,046875
Packaging Volume PL2	0,226875
Packaging Weight PL1	4,159
Packaging Weight PL2	16,636

Packaging Width PL1	125
Packaging Width PL2	275
Measurements	
Wall thickness_s	20
Z Measurement d	136,9
Z Measurement d1	125
Z Measurement e	3,1
Z Measurement L1	65

Documents

Page with all documents 

Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E
communications@georgfischer.
com