

GF HT-PP pipe with single socket S20 160x2000mm

1150116

- Gray, monolayer, PP-material, according to EN 1451. The S class is S20.



Application information GF HT-PP pipe with single socket

Specification

- The system is made from monolayer polypropylene (PP) to ensure reliable performance in standard drainage applications.
- It is designed for non-pressurized soil and wastewater drainage in residential and commercial buildings.
- The system is fully compliant with EN 1451-1 for plastic soil and waste discharge and EN 13501 for fire classification.
- It achieves fire performance rating E according to EN 13501.
- The pipes are suitable for short-term exposure to high-temperature wastewater.
- The material provides high resistance to chemicals commonly found in domestic and commercial wastewater.
- The push-fit socket design with integrated sealing rings ensures quick installation and leak-tight connections.
- The system is available in nominal diameters ranging from DN 32 to DN 200.

Application

- Residential buildings
- Office buildings and conference facilities
- Schools, libraries, hospitals, and hotels
- Underground and above-ground house drainage
- Sustainable / green building projects
- Industrial facilities (short- and long-term use)
- Wastewater from kitchens, bathrooms, and household appliances (e.g. washing machines, dishwashers)

GF HT-PP pipe with single socket S20 160x2000mm

1150116



Status

Item Available From date 2026-02-01

Product code

Item no EAN	8698652031651
Item no GF	4801016006421
Item no GTIN	08698652031651
Item no VVS	186029200

Dimensions

Item Unit Height	160
Item Unit Length	2000
Item Unit Weight	4,501
Item Unit Width	160
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414900230810
Packaging Height PL1	165
Packaging Length PL1	2005
Packaging Quantity PL1	1
Packaging Type PL1	Piece
Packaging Volume PL1	0,054586125
Packaging Weight PL1	4,601
Packaging Width PL1	165

Documents

Page with all documents

T +358 (0)20 129 211

www.uponor.com