


GF JRG lockable union, lead-free DN20

1155864

- Description: to 6320, 6325, 9910, 9920, with flat gasket
- Temperature: max. 90°C
- Nominal pressure: PN10
- Material: brass lead-free
- Connection: female thread



Application information GF JRG lockable union, lead-free

Specification


- Wide product range
- Gunmetal body

Application

Potable water installations

GF JRG lockable union, lead-free DN20

1155864



Measurements

Cylindric thread G2	1
Female thread Rp1	3/4
LENGTH_L	62
Z Measurement d	20
Z	49

Product code

Item no EAN	7613263112446
Item no GF	350887912
Item no GTIN	07613263112446

Dimensions

Item Unit Height	37
Item Unit Length	69
Item Unit Weight	0,244
Item Unit Width	40
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414900455725
Packaging GTIN PL2	06414900455732
Packaging Height PL1	37
Packaging Height PL2	120
Packaging Length PL1	69
Packaging Length PL2	180
Packaging Quantity PL1	1
Packaging Quantity PL2	10
Packaging Type PL1	Plastic_Bag
Packaging Type PL2	Medium_Box
Packaging Volume PL1	0,00010212

Packaging Volume PL2	0,002808
Packaging Weight PL1	0,26
Packaging Weight PL2	2,75
Packaging Width PL1	40
Packaging Width PL2	130

Documents

Page with all documents 

Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E
communications@georgfischer.
com