

GF Silenta HT-PP white pipe with single socket S16/S20 50x500mm

1184627

- White, monolayer, PP-material, according to EN 1451



Application information GF Silenta HT-PP white pipe with single socket S16/S20

Specification

- The system is made from monolayer polypropylene (PP) to ensure reliable performance in standard drainage applications.
- It is designed for non-pressurized soil and wastewater drainage in residential and commercial buildings.
- The system is fully compliant with EN 1451-1 for plastic soil and waste discharge and EN 13501 for fire classification.
- It achieves fire performance rating E according to EN 13501.
- The pipes are suitable for short-term exposure to high-temperature wastewater.
- The material provides high resistance to chemicals commonly found in domestic and commercial wastewater.
- The push-fit socket design with integrated sealing rings ensures quick installation and leak-tight connections.
- The system is available in nominal diameters ranging from DN 32 to DN 200.

Application

- Residential buildings
- Office buildings and conference facilities
- Schools, libraries, hospitals, and hotels
- Underground and above-ground house drainage
- Sustainable / green building projects
- Industrial facilities (short- and long-term use)
- Wastewater from kitchens, bathrooms, and household appliances (e.g. washing machines, dishwashers)

GF Silenta HT-PP white pipe with single socket S16/S20 50x500mm

1184627



Status

Item Available From date 2026-02-01

Product code

Item no EAN	6414900084970
Item no GF	4800005000321
Item no GTIN	06414900084970
Item no VVS	186022350

Dimensions

Item Unit Height	50
Item Unit Length	500
Item Unit Weight	0,197
Item Unit Width	50
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414900085557
Packaging Height PL1	400
Packaging Length PL1	800
Packaging Quantity PL1	90
Packaging Type PL1	Base_Box
Packaging Volume PL1	0,192
Packaging Weight PL1	19,29
Packaging Width PL1	600

Measurements

Z Measurement d	50
Z measurement m	50

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com