Product data sheet



GF Uponor Uni-X end plug O-ring G3/4"MT

1002273

- For use with Uni-C manifolds
- Made of plated brass
- with sealing O-Ring.



About GF Uponor Uni-X end plug O-ring

Specification

- Compression fittings with eurocone and metric connections
- Made of brass or tin-plated brass depending on variant
- Compatible with Uponor Uni Pipe PLUS and MLC pipes
- Female and male thread options according to EN ISO 228-1
- No bevel required for installation

Application

For connection of
- drinking water systems
- heating systems
- radiant heating and cooling systems

GF Uponor Uni-X end plug O-ring G3/4"MT

1002273



Product code

Item no EAN	6414905514892
Item no GTIN	06414905514892

Dimensions

Item Unit Height	15
Item Unit Length	30
Item Unit Weight	0,04
Item Unit Width	30
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905564866
Packaging Height PL1	70
Packaging Length PL1	140
Packaging Quantity PL1	50
Packaging Type PL1	Base_Box
Packaging Volume PL1	0,001666
Packaging Weight PL1	2,1
Packaging Width PL1	170

Technical documents

Download documents here

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E customerservice.uk.bfs@georgfischer.com

www.uponor.com/en-gb

+GF+