

Uponor Vario B reducer HTG 1"-1/2"

1002377

- For Vario Manifolds



About Uponor Vario B reducer HTG

Specification

- Made of brass
- With integrated valves
- Connection right or left with flat sealing supply
- With lockshield valve or flowmeter for balancing and shutoff
- no primary connection to combine it with the correct accessories
- Loop connection G3/4" eurocone
- Loop distance 50 mm
- Bracket distance 210 mm

Application

- For underfloor heating and cooling
- Combineable with actuators FT 30x1,5
- Max. pressure: 6 bar at 60°C

Uponor Vario B reducer HTG 1"-1/2"

1002377



Status

Item Available Till date

2028-12-31T00:00:00.000+0100

Product code

Item no EAN

4021598136892

Item no GTIN

04021598136892

Dimensions

Item Unit Height

40

Item Unit Length

40

Item Unit Weight

0,1

Item Unit Width

20

Item_UOM

pce

Packaging

Packaging GTIN PL1

06414900325301

Packaging Height PL1

40

Packaging Length PL1

40

Packaging Quantity PL1

1

Packaging Type PL1

Plastic_Bag

Packaging Volume PL1

0,000032

Packaging Weight PL1

0,15

Packaging Width PL1

20

Technical documents

Download documents here 

Blackmoor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb