

Uponor Vario PLUS return valve inset

1005250

- For flow regulation in return, shut-off function



About Uponor Vario PLUS return valve inset

Specification

- Modular fiberglass-reinforced polyamide manifold with 1,3,4,6 loops for connection with basic kit
- Connection right or left with flat sealing, or connection from below with optional elbow set
- Supplied with lockshield (LS) valve for balancing, or supplied with Flowmeter (FM) for balancing
- Shut-off and flow view
- Adjusting ring for balancing without tools
- Prepared are to apply room name labels
- Return with valves and caps, prepared for actuators
- Loop connection G3/4" Eurocone
- Loop pitch 50 mm
- Header pitch 225 mm

Actuator: NC (normally closed) closes without power

Application

- For underfloor heating and cooling
- Compatible with actuators MT 30x1,5

Certification

- CE

Uponor Vario PLUS return valve inset

1005250



Product code

Item no EAN	4016203787149
Item no GTIN	04016203787149
Item no LVI	2025805
Item no NRF	8361177
Item no RSK	2418980
Item no VVS	087604106

Dimensions

Item Unit Height	20
Item Unit Length	45
Item Unit Weight	0,014
Item Unit Width	20
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905251865
Packaging GTIN PL3	06414905251872
Packaging Height PL1	40
Packaging Height PL3	70
Packaging Length PL1	80
Packaging Length PL3	390
Packaging Quantity PL1	1
Packaging Quantity PL3	10
Packaging Type PL1	Plastic_Bag
Packaging Type PL3	Box
Packaging Volume PL1	0,000384
Packaging Volume PL3	0,0036855
Packaging Weight PL1	0,034
Packaging Weight PL3	0,39

Packaging Width PL1	120
Packaging Width PL3	135

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb