Product data sheet



GF Uponor Minitec connection box 1x

1005270

- For single room temperature control
- Primary circuit connection 3/4" Eurocone
- Max. pressure: 10 bar at 60°C



About GF Uponor Minitec connection box

Specification

- Minitec underfloor heating system for fixation on solid floors or specified insulation materials
- Designed as sturdy pipe fixing system of minimum height, with integrated pipe laying channels for correct pipe laying distances
- For use with Uponor Minitec PE-Xa pipes 9.9 x 1.1 mm; allowing for straight and diagonal pipe laying
- Fire class E to BS EN 13501-1 (pipe and panels)
- Pipe spacing: Vz 5, 10, 15
- Net surface with overlapping nubs: 0,77m²

Application

- Radiant underfloor heating and cooling
- Very low construction height
- For use with qualified filler materials

Certification

- DIN CERTCO: 7F170-F

GF Uponor Minitec connection box 1x

1005270



Product code

Item no EAN	4021598026735
Item no GTIN	04021598026735

Dimensions

Item Unit Height	80
Item Unit Length	300
Item Unit Weight	0,2
Item Unit Width	220
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905432400
Packaging GTIN PL4	06414905456055
Packaging Height PL1	125
Packaging Height PL4	1500
Packaging Length PL1	335
Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL4	30
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,01130625
Packaging Volume PL4	1,44
Packaging Weight PL1	0,25
Packaging Weight PL4	32,5
Packaging Width PL1	270
Packaging Width PL4	800

Technical documents

Download documents here

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E customerservice.uk.bfs@georgfischer.com

www.uponor.com/en-gb

+GF+