

Uponor Minitec connection box 1x

1005270

- For single room temperature control
- Primary circuit connection 3/4" Eurocone
- Max. pressure: 10 bar at 60°C



About Uponor Minitec connection box

Specification

- Minitec underfloor heating system for fixation on solid floors or specified insulation materials
- Designed as sturdy pipe fixing system of minimum height, with integrated pipe laying channels for correct pipe laying distances
- For use with Uponor Minitec PE-Xa pipes 9.9 x 1.1 mm; allowing for straight and diagonal pipe laying
- Fire class E to BS EN 13501-1 (pipe and panels)
- Pipe spacing: Vz 5, 10, 15
- Net surface with overlapping nubs: 0,77m²

Application

- Radiant underfloor heating and cooling
- Very low construction height
- For use with qualified filler materials

Certification

- DIN CERTCO: 7F170-F

Uponor Minitec connection box 1x

1005270



Product code

Item no EAN 4021598026735

Item no GTIN 04021598026735

Dimensions

Item Unit Height 80

Item Unit Length 300

Item Unit Weight 0,2

Item Unit Width 220

Item_UOM pce

Packaging

Packaging GTIN PL1 06414905432400

Packaging GTIN PL4 06414905456055

Packaging Height PL1 125

Packaging Height PL4 1500

Packaging Length PL1 335

Packaging Length PL4 1200

Packaging Quantity PL1 1

Packaging Quantity PL4 30

Packaging Type PL1 Base_Box

Packaging Type PL4 Pallet

Packaging Volume PL1 0,01130625

Packaging Volume PL4 1,44

Packaging Weight PL1 0,25

Packaging Weight PL4 32,5

Packaging Width PL1 270

Packaging Width PL4 800

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb