Product data sheet



GF Uponor S-Press jaw UPP1 14

1007083

- Pressing jaws for Uponor S-Press and S-Press PLUS press fittings



About GF Uponor S-Press jaw UPP1

Specification

- with fixed press sleeve
- stop ring
- test safety

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

- if not different mentioned:
Male and female threads acc.to EN 10226-1.

GF Uponor S-Press jaw UPP1 14

1007083



Product code

Item no EAN	4021598100121
Item no GF	35001007083
Item no GTIN	04021598100121

Dimensions

Item Unit Height	32
Item Unit Length	150
Item Unit Weight	1,91
Item Unit Width	105
Item_UOM	pce

Status

MTO (longer delivery times)	Item available on request, minimum lead time 2 weeks

Packaging

Packaging GTIN PL1	06414905433476
Packaging GTIN PL4	06414905456529
Packaging Height PL1	120
Packaging Height PL4	950
Packaging Length PL1	187
Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL4	280
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,0013464
Packaging Volume PL4	0,912
Packaging Weight PL1	1,99

Packaging Weight PL4	557,2
Packaging Width PL1	60
Packaging Width PL4	800

Technical documents

Download documents here

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E customerservice.uk.bfs@georgfischer.com

www.uponor.com/en-gb

+GF+